

# 8 Port AMC Managed Layer Two Switch

## SPECIFICATIONS

Architecture		
Physical	Dimensions	Single-Width, Mid-Height Front Panel (option for full-height)
		Width: 2.89 in. (73.5 mm)
		Depth: 7.11 in. (180.6 mm)
Type	AMC Ethernet	GbE switch
		Eight ports
		1 Gb/s per port
Standards		
AMC	Type	AMC.2
Module Management	IPMI	IPMI Version 2.0
1000BASE-BX	Ports	0 and 1
Configuration		
Power	AMC218	7W
Environmental	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 200 LFM) Storage Temperature: -40° to +90° C
	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connectors	MRJ-21
Front Panel	LEDs	IPMI Management Control Activity
	Mechanical	Hot Swap Ejector Handle
	Software Support	Operating Systems
Other		
MTBF	MIL Handbook 217-F > TBD Hrs.	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Compliance	RoHS and NEBS	
Warranty	Two (2) years.	
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.	