

Specifications

Architecture		
Physical	Dimensions	Single module, mid-size (full-size optional)
		Width: 2.89" (73.5 mm)
		Depth 7.11" (180.6 mm)
Type	AMC Serial USB	4 ports USB 3.0 Adapter
Standards		
AMC	Type	AMC.0
Module Management	IPMI	IPMI v2.0
USB		4 ports USB 3.0
Configuration		
Power	AMC313	3 W (without the USB device power draw)
Environmental	Temperature	See ordering options and environmental spec sheet
		Storage Temperature: -40° to +85°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30 G on each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	4x USB type C connector
		1x Micro USB for IPMI RS-232
	LEDs	IPMI management control
	Mechanical	Hot swap ejector handle
Software Support	Operating System	Independent
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.