

Architecture

Physical	Dimensions	Width: 12.687in. (322.25 mm) Depth: 11.024 in. (280 mm)
Type	IPMI Test Suite and Validation Platform	Analyzer mode Exerciser mode Compliance test mode
	VT027	VadaTech VT027 schematic implementation

Standards

Module Management	IPMI	IPMI Version 2.0
-------------------	------	------------------

Configuration

Power	ATC001	2 Watts
	Temperature	Operating Temperature: 0° to 65° C Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
Front Panel	Interface Connectors (See Ordering Options)	One USB Host port and one USB Device port Three RS-232 ports (DB9) One RS-485 port (DB9)
	LEDs	Dual 10/100 Ethernet ports with RJ-45 connectors IPMI Management Control Activity and Link
	Mechanical	Hot Swap Ejector Handle

Other

MTBF	MIL Spec 217-F > 221,000 Hrs. (VT027 option)
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.