

Architecture

Physical	Dimensions	Width: 12.687in. (322.25 mm) Depth: 11.024 in. (280 mm)
Type	ATCA Switch	26 Ports of GbE

Standards

Processor Type	MIPS	For Management
PICMG	ATCA	PICMG 3.0 R2.0
Module Management	IPMI	IPMI Version 2.0

Configuration

Power	ATC809	17W
	Temperature	Operating Temperature: 0° to 65° C (Air flow requirement is to be greater than 100 LFM) Storage Temperature: -40° to +90° C
Environmental	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connectors	8 RJ-45
Front Panel	LEDs	IPMI Management Control Link and Activity
	Mechanical	Hot Swap Ejector Handle
Software Support	Operating Systems	Independent

Other

MTBF	MIL Handbook 217-F > TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.