

Specifications

Architecture	
Physical	Dimensions 3U, Double slot
Type	cPCI GbE 12 Ports 10/100/1000 per Port
Standards	
Compact PCI	Type cPCI
Configuration	
Power	CP219 ~6W
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +90°C
	Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock Operating 30G on each axis
	Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors RJ-45 (x10)
	LEDs Run/Fail and Link/Activity
	Mechanical Hot swap ejector handle
Software Support	Operating System Independent
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.