

Specifications

Architecture	
Physical	Dimensions Single Module Width: 2.71" (69 mm) Depth: 4.09" (104 mm)
Type	FMC+ Extender for Testing and Validation Single FMC+ slot
Standards	
FMC+	Type ANSI/VITA 57.4
Configuration	
Power	FMC000 Pass thru
Environmental	Temperature -40° to +85°C Storage Temperature: -50° to +95°C Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz Shock 30Gs each axis Relative Humidity 5 to 95% non-condensing
Front Panel	Interface Connectors FMC+ connector LEDs None
Other	
MTBF	MIL Handbook 217-F@TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.