

# Specifications

Architecture	
<b>Physical</b>	<b>Dimensions</b> Single Module Width: 2.71" (69 mm) Depth: 4.09" (104 mm)
<b>Type</b>	<b>FMC+</b> Extender for Testing and Validation Single FMC+ slot
Standards	
<b>FMC+</b>	<b>Type</b> ANSI/VITA 57.4
Configuration	
<b>Power</b>	<b>FMC001</b> Pass thru
<b>Environmental</b>	<b>Temperature</b> -40° to +85°C Storage Temperature: -50° to +95°C <b>Vibration</b> Operating 9.8 m/s <sup>2</sup> (1G), 5 to 500 Hz <b>Shock</b> 30Gs each axis <b>Relative Humidity</b> 5 to 95% non-condensing
<b>Front Panel</b>	<b>Interface Connectors</b> FMC+ connector <b>LEDs</b> None
Other	
<b>MTBF</b>	MIL Handbook 217-F@TBD Hrs.
<b>Certifications</b>	Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
<b>Warranty</b>	Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.