

Architecture

Physical	Dimensions	Single-Width Width: 2.89 in. (73.5 mm) Depth: 7.11 in. (180.6 mm)
Type	μTCA JSM	21 ports

Standards

μTCA	Type	JSM
------	------	-----

Configuration

Power	μTCA	55mW
Environmental	Temperature	Operating Temperature: 0° to 65° C Storage Temperature: -40° to +90° C
Temperature	Vibration	1G, 5-500Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95 percent, non-condensing
	Interface Connectors	10 Pin right angle 0.1 spacing
	LEDs	Activity, Master port, and secondary port selection
Front Panel	Mechanical	Captive Screw tie down
Software Support	Operating Systems	Linux, Windows, Solaris and VxWorks

Other

MTBF	MIL Spec 217-F > TBD Hrs.
Certifications	Designed to meet FCC, CE and UL certifications where applicable
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Compliance	RoHS and NEBS
Warranty	Two (2) years.
Trademarks and Logos	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedMC™ and the AdvancedTCA™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.