

Specifications

Architecture		
Physical	Dimensions	Height: 6U
		6.366 x 9.187 (PCB size)
		Single slot on the base board and double slot with the daughter card
Type	Ethernet	GbE Switch
		12 Ports or 24 Ports as double slot
		10/100/1000 per Port
Standards		
VME	Type	VME
Configuration		
Power	VME218	12W Base Module
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	1G 5-500 Hz each axis
	Shock	30Gs each axis
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	RJ-45 on base board
	LEDs	Run/Fail, Link/Activity
	Mechanical	Hot-swap Ejector Handle
Software Support	Operating Systems	Independent
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.