

# Specifications

Architecture		
Physical	Dimensions	3U RTM, 1" pitch
Configuration		
Power		1W
Rear Panel	Connectors	RS-232 via Micro-USB, Dual USB via min-USB, mSATA socket
		Dual GbE, RJ-45
		PCIe x4 via Oculink
VPX Interfaces	Slot Profiles	See <a href="#">Ordering Options</a>
	Backplane	RP0: Power
		RP1: Dual GbE, RS-232, USB, 1553, SATA
		RP2: I/O
	Power Supplies	RP0: VS1 = 12V
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		Two (2) years, see <a href="#">VadaTech Terms and Conditions</a>

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.