Specifications

| Architecture | | |
|----------------|---|--------------------------------------|
| Physical | Dimensions | 3U RTM, 1" pitch |
| Configuration | | |
| Power | VRT761A | ~13W |
| Rear Panel | Connectors | Dual M.2 SATA Socket with Dual RJ-45 |
| | | RJ-45 for 10GbE Copper |
| | | M.2 SATA (internal for storage) |
| VPX Interfaces | Slot Profiles | See Ordering Options |
| | Backplane | RP0: Power |
| | | RP1: SATA and PCIe Gen3 x 4 |
| Other | | |
| MTBF | MIL Hand book 217-F@ TBD hrs | |
| Certifications | Designed to meet FCC, CE and UL certifications, where applicable | |
| Standards | VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards | |
| Warranty | Two (2) years, see VadaTech Terms and Conditions | |

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as preconfigured Application-Ready Platforms. Please contact VadaTech Sales for more information.