# VT025

# ATCA/AMC/VPX IPMI Controller, 2<sup>nd</sup> Generation



VT025

## **Key Features**

- Complete ATCA/AMC/VPX IPMI compliant reference design with software
- H8S Renesas Processor R4F2153
- 512K of Flash with 40K of SRAM
- Integrated Flash/SRAM, WDT, A/D, Quad I2C Master/Slave I2C, dual RS-232
- Payload communication via I2C
- Used on all VadaTech ATCA/AMC/VPX products
- 10x10 mm in BGA Package

## **Benefits**

- 2<sup>nd</sup> Generation IPMI Controller
- Compact size with low power consumption
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company





## **VT025**

The VT025 is a reference schematic which provides a complete hardware and software solution that occupies only a 15mm x 15mm space on the ATCA/AMC/VPX module and dissipates less than 0.2 watts. The CPU is based on Renesas H8S processor (R4F2153, packaged in a 10mm x 10mm, in BGA package) with integrated flash, quad I2C, dual RS-232, WDT, RTC, 10-bit A/D, etc.

The VT025 provides the quickest way to design for the ATCA/AMC/VPX form factor without prior IPMI knowledge. The VT025 firmware is field upgradeable and configurable via the I2C bus.

In most cases the VT025 can provide all the necessary ATCA/AMC/VPX IPMI functionality without modification. If support is required, VadaTech will provide support at minimal charge. For customers wishing to customize the binary, the VT025 development kit is all that is needed to add enhancements. The development tools are based on the GCC tool chain.

The VT025 is the most cost-effective solution in the market. The R4F2153 can be purchased from VadaTech pre-programed.

An NDA is required to obtain the reference schematic.




Figure 1: VT025

# **Specifications**

Architecture			
Physical	Dimensions	Width: 10mm	
		Length: 10mm	
Туре	AMC IPMI	Installed directly on the AMC module	
Standards			
<b>Module Management</b>	IPMI	IPMI v2.0 and PICMG 3.0	
Configuration			
Power	VT025	~200 mW	
Environmental	Temperature	See Ordering Options	
		Storage Temperature: -55° to +125°C; Operating -40° to +85°C	
	Vibration		
	Shock		
	Relative Humidity		
Others	Mechanical		
Other			
MTBF	MIL Hand book 217-F@ TBD hrs		
Certifications	Designed to meet FCC, Cl	E and UL certifications, where applicable	
Standards	VadaTech is certified to be	oth the ISO9001:2000 and AS9100B:2004 standards	
Warranty	Two (2) years, see VadaT	ech Terms and Conditions	

#### INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as preconfigured Application-Ready Platforms. Please contact VadaTech Sales for more information.

# **Ordering Options**

### VT025 - A00-000-000-XX

A = Programmed Part Architecture	
0 = Default Generic Program for AMC Architecture 1 = Default Generic Program for ATCA Architecture 2 = Default Generic Program for VPX Architecture 3 = Reserved 4 = Reserved	
	-XX (special capture)

## **Related Products**

## ATC133



- 10G ATCA Carrier
- Managed Layer 2 software
- Four full-size AMC slots





- Allows connection to shelf managers (such as VadaTech's bench-top style VT007)
- Powers a single ATCA module
- · IPMI hardware address and parity

VT830



- 19" rackmount 6U ATCA Chassis with integrated Switch and Shelf Manager
- 10GbE/GbE Managed Layer 2
- 40GbE/10GbE/GbE Managed Layer 3

## **Contact**

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014 Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhu Street, Neihu District, Taipei 114, Taiwan Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

## Choose VadaTech

## We are technology leaders

- · First-to-market silicon
- · Constant innovation
- · Open systems expertise

#### We commit to our customers

- · Partnerships power innovation
- · Collaborative approach
- Mutual success

#### We deliver complexity

- · Complete signal chain
- · System management
- · Configurable solutions

#### We manufacture in-house

- · Agile production
- · Accelerated deployment
- AS9100 accredited





#### **Trademarks and Disclaimer**

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners.

AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved.

Specification subject to change without notice.