

VT040R

Shelf Manager, 4th Generation

ATCA, MTCA and VPX platforms



VT040R

Key Features

- Quad ARM Cortex-A53 core @ 1.6 GHz per core
- 4 GB LP-DDR4 memory
- FRAM for log messages
- 64 GB of NAND Flash
- Option for 32 GB of Flash as removable SDHC
- Form, fit functional to VadaTech VT001, VT002 and VT003
- Operate across multiple platforms ATCA, MTCA and VPX like the previous generations
- Dual 10/100 Ethernet Ports
- I2C Real Time Clock with battery backup

Benefits

- 4th Generation shelf manager in mezzanine format allows use in multiple form factors
- Backwards compatibility to 3rd Generation (VT003) and earlier shelf managers
- Compact size with low (3W) power consumption
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company

Advanced TCA[®]



vadatech
THE POWER OF VISION



VT040R

The VT040R incorporates the Intelligent Platform Management Interface (IPMI v2.0) and the PICMG 3.x specification for mezzanine modules. It is VadaTech's 4th generation shelf manager product and provides a complete hardware and software solution in the size of a credit card using less than 3W.

The VT040R can be deployed on any custom management carriers for the rapid development of dedicated Shelf Managers on an ATCA, MTCA and VPX module. This allows the ATCA, MTCA and VPX module to replace a dedicated Shelf Manager, thereby reducing overall system cost.

Scorpionware™ Software

VadaTech's Scorpionware™ software can be used to access information about the current state of the Shelf or the Carrier, obtain information such as the FRU population, or monitor alarms, power management, current sensor values, and the overall health of the Shelf. The software GUI is very powerful, providing a Virtual Carrier and FRU construct for a simple, effective interface.




Figure 1: VT040R



Figure 2: VT040R Top View



Figure 3: VT040R Bottom View

Specifications

Architecture	
Physical	Dimensions Width: 2.125" (54 mm) Depth 3.375" (85.7 mm)
Type	Shelf Manager Mezzanine module to mount to a management carrier
Standards	
Module Management	IPMI IPMI v2.0 and PICMG 3.0 and VITA
Configuration	
Power	VT040R 3W
Environmental	Temperature See Ordering Options Storage Temperature: -40° to +90°C
	Vibration Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock Operating 30G each axis
	Relative Humidity 5 to 95% non-condensing
Others	Mechanical Tyco/Samtec 120 pin
Other	
MTBF	MIL Hand book 217-F@ TBD hrs
Certifications	Designed to meet FCC, CE and UL certifications, where applicable
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty	Two (2) years, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Ordering Options

VT040R – ABC-DE0-0HJ


A = SDHC Socket Flash* 0 = No socket Flash 1 = 32 GB	D = Battery 0 = Installed 1 = Not installed	
B = SPI/Modem Option 0 = SPI Interface 1 = Modem Interface 2 = SPI with MCH support	E = Heat Sink 0 = Heat spreader (Conduction Cool) 1 = Standard Air cooled (fins) 2 = Not Installed 3 = Machined Aluminium**	H = Temperature Range 1 = Commercial (Operating Temperature 0° to 65°C) 2 = Industrial
C = Flash size 0 = 64GB 1 = 128GB		J = Conformal Coating 0 = No coating 1 = Humiseal 1A33 Polyurethane 2 = Humiseal 1B31 Acrylic 3 = Parylene

Notes:

*Module does not need the SDHC flash to operate

Related Products

ATC133



- 10G ATCA Carrier
- Managed Layer 2 software
- Four full-size AMC slots

VT000



- Allows connection to shelf managers (such as VadaTech's bench-top style VT007)
- Powers a single ATCA module
- IPMI hardware address and parity

VT830



- 19" rackmount 6U ATCA Chassis with integrated Switch and Shelf Manager
- 10GbE/GbE Managed Layer 2
- 40GbE/10GbE/GbE Managed Layer 3

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhui Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited



vadatech
THE POWER OF VISION

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

© 2020 VadaTech Incorporated. All rights reserved.
DOC NO. 4FM737-12 REV 01 | VERSION 1.1 – SEP/24