

Specifications

Architecture		
Physical	Dimensions	Width: 5.89" (149.6 mm) bare module without the enclosure
		Depth 4.43" (112.5 mm) bare module without enclosure
Type	KVM	KVM over Fiber (receiver side)
Standards		
Module Management	IPMI	IPMI v2.0 and PICMG 3.0 and VITA
Configuration		
Power	VT086	15W (+5V Input)
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500 Hz on each axis
	Shock	Operating 30G each axis
	Relative Humidity	5 to 95% non-condensing
Others	Mechanical	Conduction cool with enclosure
Other		
MTBF	MIL Hand book 217-F@ TBD hrs	
Certifications	Designed to meet FCC, CE and UL certifications, where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	Two (2) years, see VadaTech Terms and Conditions	

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.