

Specifications

Architecture		
Physical	Dimensions	Width: 10"
		Depth: 5.2"
		Height: 2"
Type	Chassis	Stand alone
Configuration		
Power	VT218	~20W
Environmental	Temperature	See Ordering Options
		Storage Temperature: -40° to +90°C
	Vibration	Operating 9.8 m/s ² (1G), 5 to 500Hz on each axis
	Shock	Operating 325G/2 ms, 160G/1 ms
	Relative Humidity	5 to 95% non-condensing
Front Panel	Interface Connectors	DB-9 with +12V
		x 3 MTP/MPO for fiber
		Fan knob
Rear Panel		x12 OCuLink
Software Support	Operating System	Agnostic
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
Warranty		One (1) year, see VadaTech Terms and Conditions

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.