

SPECIFICATIONS

Architecture		
Physical	Dimensions	Height 2U
		Width 19"
		Depth 14.2"
Type	MTCA Chassis	4 MTCA.0 slots plus 4 MTCA.4 slots
Standards		
AMC	Type	AMC.1, AMC.2, AMC.3 and AMC.4
MTCA	Type	JSM, Telco Alarm, Single/Dual MCH, Single/Dual Power Module and Intelligent Cooling Unit
Configuration		
Power	VT812	500W redundant AC, or 796W DC 85-265V AC with frequency from 47-63 Hz
Environmental	Temperature	Operating Temperature: 0° to 55°C
		Storage Temperature: -40° to +70°C
	Altitude	10,000 ft operating
		40,000 ft non-operating
Relative Humidity	5 to 95% non-condensing	
Other		
MTFB	MIL Hand book 217-F @ TBD Hrs	
Certifications	Designed to meet FCC, CE and UL certifications where applicable	
Standards	VadaTech is certified to both the ISO9001:2015 and AS9100D standards	
Warranty	One (1) year, see VadaTech Terms and Conditions	
Trademarks and Disclaimer	The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice	

REAR VIEW

