

# Specifications

Architecture		
<b>Physical</b>	<b>Dimensions</b>	Height: 2U Width: 19" Depth: 12.5" Weight: TBD
<b>Type</b>	<b>VPX</b>	3 Payload Slot up to 1.0" pitch
Standards		
<b>VPX</b>	<b>Type</b>	VITA 46.0 Baseline Specification
Configuration		
<b>Power</b>	<b>VTX882</b>	900W DC +28V input
<b>Environmental</b>		See <a href="#">Ordering Options</a>
<b>Cooling</b>		Front to back
<b>Power Limit</b>	<b>Payload for three slots</b>	600W
Other		
<b>MTBF</b>		MIL Hand book 217-F@ TBD hrs
<b>Certifications</b>		Designed to meet FCC, CE and UL certifications, where applicable
<b>Standards</b>		VadaTech is certified to both the ISO9001:2015 and AS9100D standards
<b>Warranty</b>		One (1) year, see <a href="#">VadaTech Terms and Conditions</a>

OpenVPX allows for a wide range of pin assignments and use cases. Prior to purchasing VadaTech products as standalone items (i.e., not part of an integrated platform) please consult with VadaTech on the system architecture to ensure compatibility.

## INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.