

VTX982

One Slot 3U VPX Benchtop Development Chassis with RTM (P2 with VITA 67.2)

Key Features

- One slot benchtop 3U VPX development platform
- P2 with VITA 67.2 connector option
- Variable fan speed control for front and rear
- Removable panels for ease of access for probing
- Support for Rear Transition Modules (RTMs)
- Allows for a shelf manager to do health monitoring
- JTAG connector
- User setting of SYSRESET, NVMRO, etc.
- On board battery pack to provide the VBAT
- Vertical or Horizontal positioning on bench

Benefits

- Optional shelf manager supporting Tier 2 Health Management
- 750 W AC Power supply
- Ease of access to board under development
- Electrical, mechanical, software, and system-level expertise in house
- Full system supply from industry leader
- AS9100 and ISO9001 certified company



vadatech
THE POWER OF VISION



VTX982

The VTX982 is a single slot 3U VPX chassis for board bring-up and testing of 3U VPX modules. The chassis can accept a front and a rear module (5HP or 10HP). The panels on both the front and rear slots are removable for ease of probing and debugging. The P2 connector has option for VITA 67.2.

The VTX982 can be placed on bench in both horizontal and vertical positioning for ease of access.

Power Supply

The VTX982 comes with a Universal AC power supply which provides 750 W to the chassis. The chassis supplies all the necessary power (+12 V, -12 V, +5 V, etc.) to the module in accordance with VITA 46 specifications.

VTX982 also comes with a battery pack which provides the VBAT to the module. The VTX982 allows the power to VBAT to be switched between the on-board battery pack and the power supply. Each of the rails have a sense resistor to allow the user to monitor how much power is being drawn from each rail using a simple voltmeter.

Cooling

The VTX982 provides cooling to the module via a variable fan speed for both front and rear.

Backplane

The backplane provides all the necessary VITA 46 signals set by the user (NVMRO, SYSRESET, SYS_CON, driver the dual clock, etc.). All the connectors are installed P0 thru P2 and are routed from the front to the rear.

Health Monitoring

The dual IPMI bus is routed to a connector compatible with an external VadaTech VT007 bench top shelf manager for monitoring the VPX board sensors, compliance to VITA 46.11, etc. The VT007 supports Tier 2 Health Management and can be ordered separately or as an option with VTX982.

JTAG

The backplane brings out the JTAG signals to a header to allow connection to an external JTAG probe.

Specifications

Architecture		
Physical	Dimensions	Height: 3U
Standards		
VPX	Type	VITA 46.0 and VITA 67.2
Configuration		
Power	VTX982	750 W AC universal
Environmental		See ordering options
Cooling		Right to left
Other		
MTBF		MIL Hand book 217-F@ TBD hrs
Certifications		Designed to meet FCC, CE and UL certifications, where applicable
Standards		VadaTech is certified to both the ISO9001:2000 and AS9100B:2004 standards
Warranty		Two (2) years

INTEGRATION SERVICES AND APPLICATION-READY PLATFORMS

VadaTech has a full ecosystem of OpenVPX, ATCA and MTCA products including chassis platforms, shelf managers, AMC modules, Switch and Payload Boards, Rear Transition Modules (RTMs), Power Modules, and more. The company also offers integration services as well as pre-configured Application-Ready Platforms. Please contact VadaTech Sales for more information.

Ordering Options

VTX982 – AB0-000-0HJ

A = Power supply 0 = 750 W (AC)		
B = Shelf Manager (health monitoring) 0 = No VT007 1 = VT007 included		H = Environmental See Environmental Specification Table below
		J = Conformal Coating 0 = No coating 1 = Humiseal 1A33 polyurethane 2 = Humiseal 1B31 acrylic

Environmental Specification*

Option H	H = 0
Operating Temperature	-5°C to +55°C
Storage Temperature	-40°C to +85°C
Operating Vibration	0.04 g2/Hz max
Storage Vibration	20g
Humidity	95% non-condensing

*Please contact VadaTech Sales for other specification

Related Products

VPX551



- Dual Kintex UltraScale™ XCKU115
- 16 GB of 64-bit wide DDR4 Memory to each FPGA
- Rear fibre I/O via VITA 66.5

VPX645



- 3U VPX NVMe Host Bus Adapter with Full support for RAID
- Dual Core ARM A15 RAID on Chip (ROC)
- On board 8 GB of DDR4 Memory with ECC

VPX752



- 6U VPX module Intel 5th Generation Xeon-D SoC
- PCIe Gen3 x16 (dual x8 or quad x4)
- Quad 10GbE XAUI

Contact

VadaTech Corporate Office

198 N. Gibson Road, Henderson, NV 89014

Phone: +1 702 896-3337 | Fax: +1 702 896-0332

Asia Pacific Sales Office

7 Floor, No. 2, Wenhua Street, Neihu District, Taipei 114, Taiwan

Phone: +886-2-2627-7655 | Fax: +886-2-2627-7792

VadaTech European Sales Office

VadaTech House, Bulls Copse Road, Southampton, SO40 9LR

Phone: +44 2380 016403

info@vadatech.com | www.vadatech.com

Choose VadaTech

We are technology leaders

- First-to-market silicon
- Constant innovation
- Open systems expertise

We commit to our customers

- Partnerships power innovation
- Collaborative approach
- Mutual success

We deliver complexity

- Complete signal chain
- System management
- Configurable solutions

We manufacture in-house

- Agile production
- Accelerated deployment
- AS9100 accredited



vadatech
THE POWER OF VISION

Trademarks and Disclaimer

The VadaTech logo is a registered trademark of VadaTech, Inc. Other registered trademarks are the property of their respective owners. AdvancedTCA™ and the AdvancedMC™ logo are trademarks of the PCI Industrial Computers Manufacturers Group. All rights reserved. Specification subject to change without notice.

© 2018 VadaTech Incorporated. All rights reserved.
DOC NO. 4FM737-12 REV 01 | VERSION 1.2 – DEC/18